



## Features

- **Aluminum Frame, Rugged Design**
- **High Efficiency Solar Cells Up to 9.85 Amp, Continuously recharge your 12V batteries with the power of the sun.**
- **Includes, charge controller, battery connecting cable and mounting Z-brackets**
- **Connect additional panels for a faster charge**
- **Requires a charge controller to protect batteries from overcharging**



## SPECIFICATIONS

### Solar Panel

Solar Panel: Crystalline

Maximum Power : 200 Watt

Voltage at Pmax(Vmp): 20.31 V

Current at Pmax(Imp): 9.85A

Open circuit voltage(Voc): 24.35 V

Short circuit Current(Isc): 10.33 A

Operating Temperature: -40°C to + 85°C

### Charge Controller

Maximum Solar Input: <50V

Maximum Input Current: 13 A

Battery Voltage: 12V/24V Auto

USB Out put: 5V/3A

**Material:** Aluminum, Glass construction & Steel

## SHIPPING DETAILS

Item Number: 50200

UPC Code: 839290005842

Country of Origin: Indonesia

Panel Dimensions: 61.4 x 28.1 x 1.4 in

Package Dimensions: 67 x 28.9 x 2.6 in

Product Weight: -lbs with package

26.5 lbs without package

Master Quantity: 1

Master Dimensions: 67 x 28.9 x 2.6 in

Master Weight: - lbs



**1-800-588-0590**

[www.naturepowerproducts.com](http://www.naturepowerproducts.com)



[fb.me/NaturePowerProducts](https://fb.me/NaturePowerProducts)

