



40W MONOCRYSTALLINE BRIEFCASE SOLAR PANEL



2 x Stand Poel



12V Battery Charge Controller Attached to Panel



SAE Polarity Adapter



SAE to battery clamps cable 1.5mm² / 1 meter



SAE to Bare end cable 1.5mm² / 3 meter

Features

- **Aluminum Frame, Rugged Design**
- **High Efficiency Solar Cells Up to 2.22 Amp, Continuously recharge your 12V batteries with the power of the sun**
- **Includes charge controller and battery connecting cable**
- **Connect additional panels for a faster charge**
- **Easily folds into a briefcase for easy storage and Transportation**

SPECIFICATIONS

| |
|---|
| Solar Panel: 40 Watt Monocrystalline |
| Maximum Power: 40 Watt |
| Maximum System Voltage: 600V |
| Current at Pmax(Imp): 2.22 A |
| Votage at Pmax(Vmp): 18.0V |
| Short circuit current(Isc): 2.44 A |
| Open Circuit Voltage(Voc): 21.2V |
| Tolerance: ± 3% |
| Operating Temperature: -40°C to + 85°C |
| Material: Aluminum, Glass constrction & Steel |

SHIPPING DETAILS

| |
|---|
| Item Number: 55701 |
| UPC Code: 839290005323 |
| Country of Origin: Vietnam |
| Panel Dims LxWxH(Close): 15.6 x 2.32 x 16.7 in |
| Color box Dims LxWxH: 16 x 2.45 x 17 in |
| Product Weight: 12.2 lbs with packge 10.1 lbs without packge |
| Master Quantity: - |
| Master Dimensions: - in |
| Master Weight: - lbs |



1-800-588-0590
www.naturepowerproducts.com

fb.me/NaturePowerProducts

